

DETAILS

Type: Polyurethane, Solvent, 1K

Use: Interior Floor

Finish: Gloss

Surface: Concrete / Mortar

Method: Brush / Roller

Painting Interval (23°C): 3 - 48 hrs.

Walk-able: 16 hrs.


Fully Cured: 3 days

Performance: 2 - 6 yrs.

Coverage: 137 m² / 16kg can / coat

Coverage: 35 m² / 4kg can / coat

**A TRADITION OF
OUTSTANDING
JAPANESE
TECHNOLOGY.
PAINT IT ECO.**



**MIZUTANI PAINT
PHILIPPINES INC.**

M. Greenfield Industrial Complex
Merville Access Road, Paranaque City

www.mizutanippi.com
info@mizutanippi.com
632.809.1316



**BOUJINTEX
MARK STOP**

1K SOLVENT POLYURETHANE
ANTI-POLLUTION



DESCRIPTION

BOUJINTEX MARK STOP is a one-component, solvent type, polyurethane floor paint that can be applied as topcoat of different floor paints. As well as coating for bare mortar or concrete surfaces. It prevents contamination from heel or tire marks caused by forklifts due to the special resin that is rich in scratch resistance.

USE

BOUJINTEX MARK STOP is suitable for a hallway, lobby, office, warehouse, factory, electric room, indoor parking, automobile shop, and many more.

Can be used as topcoat for:

- BOUJINTEX #2000
- BOUJINTEX #8000
- BOUJINTEX #5000U
- BOUJINTEX #5000U HARD-COAT
- BOUJINTEX MARK-STOP
- Mortar, Concrete-floor

FEATURES & ADVANTAGES

1. Anti-Pollution
- excellent scratch and stain resistance
2. Clear high gloss finish
- can be applied as top coat for different floor coatings or bare concrete/mortar.
3. One component
- economical, easy application by brush or roller.
4. Abrasion resistant - fights wear and tear.
5. Dust proof - achieves a tough and appealing fine finish.