

# DETAILS

Type: Epoxy, Solvent Type, 2K

Use: Interior Floor

Finish: Gloss

Surface: Mortar / Concrete

Method: Brush / Roller

Painting Interval (23°C): 6 hrs.

Walk-able: 16 hrs.


Fully Cured: 2 days

Performance: 2 - 6 yrs.

Coverage: 90 m2 / 16 kg set / coat

Coverage: 23 m2 / 4 kg set / coat

**A TRADITION OF  
OUTSTANDING  
JAPANESE  
TECHNOLOGY.  
PAINT IT ECO.**



**MIZUTANI PAINT  
PHILIPPINES INC.**

M. Greenfield Industrial Complex  
Merville Access Road, Paranaque City

www.mizutanippi.com  
info@mizutanippi.com  
632.809.1316



**BOUJINTEX  
#2000**

2K SOLVENT BASED EPOXY  
HEAVY DUTY



# DESCRIPTION

BOUJINTEX #2000 is a two-component, epoxy floor coating that can be applied on mortar and concrete surfaces. It has outstanding performance in durability due to the combined adhesion of epoxy resin and a specially modified polyamine resin.

BOUJINTEX #2000 can resist water, chemical, and oil. A floor coating that is particularly strongest in wear resistance, capable of withstanding frequent traffic and transport of heavy loads.

BOUJINTEX #2000 is the reliable and sustainable solution for establishments that can't afford interruptions with its' daily operations. It is an essential foundation that can contribute to growth and productivity.

## USE

BOUJINTEX #2000 IS IDEAL FOR HIGH TRAFFIC INDOOR FLOORS THAT REQUIRE HIGH ABRASION RESISTANCE, SUCH CHEMICAL PLANTS, PRINTING FACTORIES, ELECTRIC ROOMS, KITCHENS, PASSAGEWAYS, CAR PARKS, WAREHOUSES WITH LIFTS, GARAGE, AND BUSY FACTORIES IN GENERAL.



## FEATURES & ADVANTAGES

1. Heavy duty
  - can withstand heavy foot traffic.
2. Multi-functional
  - has a wide range of applications.
3. Abrasion resistant
  - fights wear and tear.
4. Chemical and oil resistant
  - endures harsh environment.
5. Dust proof
  - achieves a tough and appealing fine finish.