

DETAILS

Type: Epoxy, Solvent Based, 2K

Use: Interior Floor

Finish: Gloss

Surface: Mortar / Concrete

Method: Brush / Roller

Painting Interval (23°C): 8 - 48 hrs.

Walk-able: 16 hrs.

Fully Cured: 3 days

Coverage: 95 m² / 15 kg set / coat

**A TRADITION OF
OUTSTANDING
JAPANESE
TECHNOLOGY.
PAINT IT ECO.**



**MIZUTANI PAINT
PHILIPPINES INC.**

M. Greenfield Industrial Complex
Merville Access Road, Paranaque City

www.mizutanippi.com
info@mizutanippi.com
632.809.1316



**BOUJINTEX
#2700DG**

2K SOLVENT BASED EPOXY
ANTI-STATIC



DESCRIPTION

Mizutani Paint Philippines Inc.'s BOUJINTEX #2700DG is Japanese quality epoxy floor paint with a special anti-static feature that prevents electrostatic charging and static electricity accidents in factories and offices.

BOUJINTEX #2700DG provides safety control in production areas, factories, operating rooms, and computer rooms.

USE

BOUJINTEX #2700DG is suitable for a factory, fine particle warehouse, and gunpowder warehouse, where electronic parts are made. As well as a computer room, clean room, and operation room.

FEATURES & ADVANTAGES

1. Static Electricity Prevention
2. Durable & Wear Resistant
3. Chemical & Oil Resistant
4. Dust Proof - Achieves a tough and appealing fine finish.