

DETAILS

Type: Epoxy, Solvent Based, 2K

Use: Interior Floor

Finish: High Gloss

Surface: Mortar / Concrete

Method: Squeegee / Trowel

Painting Interval: 16 - 48 hrs.

Walk-able: 16 hrs.


Fully Cured: 2 days

Performance: 3 - 10 yrs.

Coverage: 11 m² / 15 kg set @ 1

mm (Flat Finish)

**A TRADITION OF
OUTSTANDING
JAPANESE
TECHNOLOGY.
PAINT IT ECO.**



**MIZUTANI PAINT
PHILIPPINES INC.**

M. Greenfield Industrial Complex
Merville Access Road, Paranaque City

www.mizutanippi.com
info@mizutanippi.com
632.809.1316



**BOUJINTEX
#8000**

2K SOLVENT BASED EPOXY
SELF LEVELLING



DESCRIPTION

BOUJINTEX #8000 is a high build, solvent type, epoxy coating for interior floors. It has excellent self levelling properties that create a tough coating with a high gloss finish.

BOUJINTEX #8000 is a thick film coating with strong performance in durability and chemical resistance. It can fully withstand activity in harsh places by exhibiting particular wear resistance, water resistance, chemical resistance, and oil resistance, which are unique to epoxy resin.

USE

1. Factories and warehouses requiring toughness, durability, and abrasion resistance.
2. Vehicle passages requiring toughness, durability, and wear resistance.
3. Factories and laboratories handling food and chemicals.
4. Machine factory and manufacturing plant that often use oil.
5. Car repair shop.
6. Food factory, hospital room, examination room, etc.
7. Floor requiring antibacterial features.

FEATURES & ADVANTAGES

1. Self levelling.
2. High gloss luxury finish.
3. Durable thick film coating.
4. Good abrasion resistance.
5. Excellent in water, chemical, & oil resistance.
6. Various specifications available depending on requirements.
7. Antibacterial specification is also possible.