

# DETAILS

Type: Epoxy, Water Based, 2K

Use: Interior Floor

Finish: Gloss

Surface: Mortar / Concrete

Method: Brush / Roller

Painting Interval: 10 - 48 hrs.

Walk-able: 14 hrs.

Fully Cured: 2 days

Performance: 2 - 6 yrs.

Coverage: 95 m<sup>2</sup> / 14 kg set / coat

Coverage: 28 m<sup>2</sup> / 4 kg set / coat

**A TRADITION OF  
OUTSTANDING  
JAPANESE  
TECHNOLOGY.  
PAINT IT ECO.**



**MIZUTANI PAINT  
PHILIPPINES INC.**

M. Greenfield Industrial Complex  
Merville Access Road, Paranaque City

[www.mizutanippi.com](http://www.mizutanippi.com)  
[info@mizutanippi.com](mailto:info@mizutanippi.com)  
632.809.1316



**MIZUKEI  
BOUJINTEX  
E**

2K WATER-BASED EPOXY  
ECO & DURABLE

# DESCRIPTION

MIZUKEI BOUJINTEX E is a two-component, water based, epoxy floor paint that can be applied on mortar and concrete surfaces. It has performance comparable to the strength of solvent-based epoxy, and provides the highest level of gloss in the water-based system.

MIZUKEI BOUJINTEX E is an Eco-friendly interior floor paint that is safe for the surroundings, but still as reliable. Ideal for enclosed areas that can't use solvents, but require tough and durable coatings such as underground car parks, basements, and the like.

## USE

MIZUKEI BOUJINTEX E is ideal for enclosed areas where flammable products are not safe for use, such as underground car parks, basements, shops, and the like.



## FEATURES & ADVANTAGES

1. Durable & Tough
  - Comparable strength to solvent type epoxy
2. Water based
  - Eco-friendly, releases low odor, and prevents danger of fire or solvent intoxication.
3. Abrasion resistant
  - fights wear and tear caused by frequent traffic.
4. Dust proof
  - achieves a tough and appealing fine finish.